
Item Code: 100-076/LTGN-500









| X EC Verified | |
|-----------------------|--|
| X Choice of colour | |
| X Choice of reel size | |
| X Fast feed box | |

X Sequential metre markings

Product Overview

Excel Category 6 Screened cables are manufactured and tested to the TIA/EIA 568-B.2-1, EN50173-1 and ISO/ IEC 11801 Category 6 specifications. Each cable consists of 8 colour coded polyethylene insulated conductors. These are twisted together to form 4 pairs with varying lay lengths. These pairs are then formed around a central ?X? shaped polyethylene filler, which assists in maintaining and enhancing the cable's performance.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

Product Specifications


| Feature | Values |
|---|-------------|
| Category | 6 |
| Overall screening | Foil |
| Conductor screening | None |
| Outer sheath colour | Light Green |
| Reaction-to-fire class according to EN 13501-6 | Dca |
| Smoke development class according to EN 13501-6 | s2 |
| Euro class flaming droplets/particles according to EN 13501-6 | d2 |
| Euro class acidity according to EN 13501-6 | al |
| AWG-size | 23 |
| Specification core insulation | PE |
| Core identification | Colour |

Item Code: 100-076/LTGN-500



| Outer sheath material | Copolymer |
|----------------------------------|--|
| Halogen free (acc. EN 60754-1/2) | Yes |
| Flame retardant | In accordance with EN 60332-1-2 and EN 50399 |
| Outer diameter approx. | 7.2 mm |
| Installation Temperature Range | 050 °C |
| Operating Temperature Range | -1060 °C |
| NVP value | 72 % |
| RAL-number | 6027 |
| Conductor category | Class $1 = solid$ |
| Total number of cores | 8 |
| Stranding element | Pairs |
| Conductor surface | Bare |

Cross-section diagram



Cable specifications

| Features | Values |
|-------------------------|--------------|
| Dielectric strength | 2.5kV for 2s |
| Maximum Pulling Load | 60N/6.1KgF |
| MBR during installation | 8x cable OD |
| MBR installed | 4x cable OD |

Item Code: 100-076/LTGN-500



Standards

| Applicable standard | Subject |
|-------------------------------|--|
| ISO/IEC 11801-1:2017 | Information technology - Generic cabling for customer premises: Part 1 General Requirements |
| IEC 61156-5:2020 | Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification |
| EN 50173-1:2018 | Information technology. Generic cabling systems - General requirements |
| EN 50173-2:2018 | Information technology. Generic cabling systems - Office premises |
| BS EN 50288-6-1:2013 | Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz |
| EN 50399:2011+A1:2016 | Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results |
| IEC 60332-1-2:2004 + A12:2020 | Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for $1\ kW$ pre-mixed flame |
| ANSI/TIA 568-D:2015 | Balanced Twisted-Pair Telecommunications Cabling and Components Standards |
| IEC 60754-2:2014 | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity |
| IEC 61034-2:2005+A1:2013 | Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements |
| EN 50575:2014 + A1:2016 | Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements |
| RoHS | Restriction of Hazardous Substances - Compliant |
| | |

Item Code: 100-076/LTGN-500



Part Number Table

| Part Number | Description |
|------------------|--|
| 100-076 | Excel Category 6 Cable F/UTP Dca LS0H 305m Reel - Violet |
| 100-076/LTGN-500 | Excel Category 6 Cable F/UTP Dca LS0H 500m Reel - Light Green |
| 100-076-1000 | Excel Category 6 Cable F/UTP Dca LS0H 1000m Reel - Violet |
| 100-076-305M-GN | Excel Category 6 Cable F/UTP Dca LS0H 305m Easyreel - Green |
| 100-077/LTGN | Excel Category 6 Dual Cable F/UTP Dca LS0H 500m Reel - Light Green |
| 190-076 | Excel Category 6 Cable F/UTP B2ca LS0H 305m Reel - Violet |
| 190-076/LTGN-500 | Excel Category 6 Cable F/UTP B2ca LS0H 500m Reel - Light Green |
| 190-076-305M-GN | Excel Category 6 Cable F/UTP B2ca LS0H 305m Easyreel Box - Green |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

