



LogiLink®
www.LogiLink.com

Network Cameras





WC0007

WC0006/WC0007

Wired/Wireless 11N Pan-Tilt Network Camera

- Compliant to Wireless 802.11b/g/n technology (WC0007)
- Camera/Image:
 - Dual Mode: MPEG4 and Motion-JPEG Image Video
 - Multiple Profile: Output M-JPEG and MPEG4 in the same time
 - Multi-area motion detection
 - Web UI Remote Pan-Tilt Control
 - Supports SD card for local recording
 - Event Trigger: Mail & FTP
 - 2-way audio
 - High Speed Hardware-Based Image Compression
 - Image sensor: 1.3M Pixels CMOS Sensor
 - Manual Focus lens, F=2.8
- Utility:
 - Includes easy-to-use Viewer & Recorder utility
 - Provide Admin utility, Camera Viewer & WEB browser Management
 - View multiple cameras simultaneously - Up to 16 at a time
 - Supports four additional user accounts for viewing camera
 - Manual/Schedule/Cycle Record, Video Playback/Forward/Pause/Stop
 - Auto sending Snapshot to E-mail & FTP
 - Supports Windows 2000/XP/Vista/7
 - Firmware Upgradeable



WC0041

WC0040/WC0041

Wired/Wireless 11N Network Camera

- Compliant to Wireless 802.11b/g/n technology (WC0041)
- Camera/Image:
 - Dual Mode: MPEG4 and Motion-JPEG Image Video
 - Multiple Profiles: Output M-JPEG and MPEG4 at the same time
 - Multi-area Motion Detection
 - Provides Fixed Focus Lens, $F = 2.8$
 - Supports Up to 30 fps Video Frame Rate
 - High Speed Hardware-Based Image Compression
- HTTP/Utility:
 - Includes easy-to-use Viewer & Recorder utility
 - Provide Admin utility, Camera Viewer & WEB browser Management
 - Support Wireless 802.11b/g/n Standard
 - View multiple cameras simultaneously - Up to 16 at a time
 - Supports 4 additional user accounts for viewing camera
 - Manual/Schedule/Cycle Record, Video Playback/Forward/Pause/Stop
 - Auto Sending Snapshots by E-mail and FTP
 - Firmware Upgradeable
 - Supports Windows 2000/XP/Vista/7



WC0010/WC0010A Network Camera, H.264

- WC0010: 1/3.6" H.R. CMOS image sensor
- WC0010A: 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768 (H) x 494 (V), PAL: 752 (H) x 582 (V)
- Low-latency video streaming for sharp & clear images
- MPEG4, MJPEG and H.264 compression
- Hybrid Digital / Analog video output
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time

Optional:

WC0010 Network Camera (for MJPEG/MPEG4 only)



WC0013

Wired/Wireless Day/Night IP Camera, H.264

Support Wireless with an optional USB WiFi dongle

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768 (H) x 494 (V), PAL: 752 (H) x 582 (V)
- Low-latency video streaming for sharp & clear images
- MPEG4, MJPEG and H.264 compression
- Hybrid Digital / Analog video output
- Motion detection and alarm notification via Email
- External microphone in / audio out for two-way voice communication
- Day & night functionality with built-in Infrared LEDs and Smart Light Control feature for clear and accurate image
- Supports wireless function with an optional USB wireless dongle via USB port
- 802.11b/g/n wireless standard
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time



WC0014/WC0014C

Outdoor IP Dome Camera, H.264

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768 (H) x 494 (V) ; PAL: 752 (H) x 582 (V)
- Advanced Auto Tracking Accuracy - to follow the moving object
- MPEG4, MJPEG and H.264 compression
- Supports 360 degree pan and 90 degree tilt, continuous rotation
- 22x Zoom F1.6 (wide) ~ F3.7(Tele), view: 60°~4°
- Flexible Color / Shutter Parameters Adjustment - to adapt various light conditions
- Outdoor IP Rating with IP66
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time

Optional:

WC0014 Outdoor IP Dome Camera for MJPEG/MPEG4 only



WC0015

Outdoor IR IP Camera, H.264, with Optical Smart Zoom and Vari-focal Lens

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768(H) x 494(V), PAL: 752(H) x 582(V)
- MPEG4, MJPEG and H.264 compression
- Smart Zoom: zoom in on the object that triggered the alarm
- True Day & Night surveillance with IR shifter & large aperture lens (F1.8)
- Vari-focal Lens f4.0mm ~ f9.0mm, View: 75° ~ 36°
- Outdoor IP Rating with IP67
- Longer IR effective distance up to 40 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Durable 56 IR LEDs built-in application
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time



WC0016

Outdoor IR IP Camera, H.264

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768 (H) x 494 (V), PAL: 752 (H) x 582 (V)
- MPEG4, MJPEG and H.264 compression
- True Day & Night surveillance with IR shifter & large aperture lens (F1.4)
- Outdoor IP Rating with IP67
- Longer IR effective distance up to 40 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Durable 56 IR LEDs built-in application
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time



WC0017

1.3 Megapixel Outdoor IR IP Camera, H.264

- 1/3" Live MOS image sensor
- Resolution: 1280(H) x 1024 (V)
- MPEG4, MJPEG and H.264 compression
- True Day & Night surveillance with IR shifter & large aperture lens
- Outdoor IP Rating with IP67
- Longer IR effective distance up to 25 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Smart Zoom: zoom in on the object that triggered the alarm
- Excellent outdoor ID design with cable management
- Durable 56 IR LEDs built-in application
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Supports Face Tracking
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same Time



WC0018

IP Dome Camera with Optical Smart Zoom, H.264

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 771 (H) x 492 (V) ; PAL: 753 (H) x 582 (V)
- Advanced Auto Tracking Accuracy - to follow the moving object
- MPEG4, MJPEG and H.264 compression
- Smart Zoom: zoom in on the object that triggered the alarm
- Supports 360 degree pan and 90 degree tilt, continuous rotation
- 2.25x Zoom F1.8 f4.0mm ~ f9.0mm View:75°~36°
- Flexible Color / Shutter Parameters Adjustment - to adapt various light conditions
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time



WC0019

Outdoor IP Dome Camera with 22x PTZ, H.264

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768 (H) x 494 (V) ; PAL: 752 (H) x 582 (V)
- Advanced Auto Tracking Accuracy - to follow the moving object
- MPEG4, MJPEG and H.264 compression
- Supports 360 degree pan and 90 degree tilt, continuous rotation
- 22x Zoom F1.6 (wide) ~ F3.7(Tele), view: 60°~4°
- Flexible Color / Shutter Parameters Adjustment - to adapt various light conditions
- Outdoor IP Rating with IP66
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports Auto Tracking
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time

Control Network Camera Via Central Management System (CMS)



- One powerful interface to remotely control multiple-channel network surveillance devices
- Multiplex operation simultaneously in one interface, such as live viewing, playback, recording and backup
- Fluent & clear images for remote surveillance (MPEG4 or H.264 network transmission)
- Full evidence capturing with advanced recording functions (motion detection / pre- & post-alarm recording) when an event occurred

LogiLink[®]